

Bistable switches RBS

Bistable Switch RBS

Description

REMOTE SWITCHING AND AUTOMATIC CONTROL:

- Lightning
- Electric heating
- Electric motors
- Electric equipment


ADVANCED OPERATION:

- Impulse control
- Manual control


OTHER BENEFITS:

- Small switch on coil consumption
- No hold coil consumption
- Wide application
- Mounting on 35 mm rail
- Sealing terminal covers


1-pole, 1 module (17,5 mm), 20A (AC1, 440V)

Type	Code No.	Wiring diagram	Weight [g]	Packaging [pcs]
RBS220-10-230V AC	002464100		130	8
RBS220-10-24V AC	002464112		130	8

1-pole, 1 module (17,5 mm), 25A (AC1, 440V)







Type	Code No.	Wiring diagram	Weight [g]	Packaging [pcs]
RBS225-10-230V AC	002464101		130	8
RBS225-10-24V AC	002464113		130	8

1-pole, 1 module (17,5 mm), 32A (AC1, 440V)







Type	Code No.	Wiring diagram	Weight [g]	Packaging [pcs]
RBS232-10-230V AC	002464102		130	8
RBS232-10-24V AC	002464114		130	8









2-pole, 1 module (17,5 mm), 20A (AC1, 440V)

Type	Code No.	Wiring diagram	Weight [g]	Packaging [pcs]
RBS220-20-230V AC	002464103		130	8
RBS220-20-24V AC	002464115		130	8
RBS220-11-230V AC	002464106		130	8
RBS220-11-24V AC	002464118		130	8
RBS220-1C-230V AC	002464109		130	8
RBS220-1C-24V AC	002464121		130	8

2-pole, 1 module (17,5 mm), 25A (AC1, 440V)

Type	Code No.	Wiring diagram	Weight [g]	Packaging [pcs]
RBS225-20-230V AC	002464104		130	8
RBS225-20-24V AC	002464116		130	8
RBS225-11-230V AC	002464107		130	8
RBS225-11-24V AC	002464119		130	8
RBS225-1C-230V AC	002464110		130	8
RBS225-1C-24V AC	002464122		130	8

2-pole, 1 module (17,5 mm), 32A (AC1, 440V)

Type	Code No.	Wiring diagram	Weight [g]	Packaging [pcs]
RBS232-20-230V AC	002464105		130	8
RBS232-20-24V AC	002464117		130	8
RBS232-11-230V AC	002464108		130	8
RBS232-11-24V AC	002464120		130	8
RBS232-1C-230V AC	002464111		130	8
RBS232-1C-24V AC	002464123		130	8

Bistable switches RBS

3-pole, 2 modules (35 mm), 20A (AC1, 440V)

Type	Code No.	Wiring diagram	Weight [g]	Packaging [pcs]
RBS420-21-230V AC	002464127		200	4
RBS420-21-24V AC	002464145		200	4
RBS420-30-230V AC	002464130		200	4
RBS420-30-24V AC	002464148		200	4

3-pole, 2 modules (35 mm), 25A (AC1, 440V)

Type	Code No.	Wiring diagram	Weight [g]	Packaging [pcs]
RBS425-21-230V AC	002464128		200	4
RBS425-21-24V AC	002464146		200	4
RBS425-30-230V AC	002464131		200	4
RBS425-30-24V AC	002464149		200	4

3-pole, 2 modules (35 mm), 32A (AC1, 440V)

Type	Code No.	Wiring diagram	Weight [g]	Packaging [pcs]
RBS432-21-230V AC	002464129		200	4
RBS432-21-24V AC	002464147		200	4
RBS432-30-230V AC	002464132		200	4
RBS432-30-24V AC	002464150		200	4

4-pole, 2 modules (35 mm), 20A (AC1, 440V)

Type	Code No.	Wiring diagram	Weight [g]	Packaging [pcs]
RBS420-40-230V AC	002464124		200	4
RBS420-40-24V AC	002464142		200	4
RBS420-31-230V AC	002464133		200	4
RBS420-31-24V AC	002464151		200	4
RBS420-22-230V AC	002464136		200	4
RBS420-22-24V AC	002464154		200	4
RBS420-2C-230V AC	002464139		200	4
RBS420-2C-24V AC	002464157		200	4



4-pole, 2 modules (35 mm), 25A (AC1, 440V)

Type	Code No.	Wiring diagram	Weight [g]	Packaging [pcs]
RBS425-40-230V AC	002464125		200	4
RBS425-40-24V AC	002464143		200	4
RBS425-31-230V AC	002464134		200	4
RBS425-31-24V AC	002464152		200	4
RBS425-22-230V AC	002464137		200	4
RBS425-22-24V AC	002464155		200	4
RBS425-2C-230V AC	002464140		200	4
RBS425-2C-24V AC	002464158		200	4

4-pole, 2 modules (35 mm), 32A (AC1, 440V)

Type	Code No.	Wiring diagram	Weight [g]	Packaging [pcs]
RBS432-40-230V AC	002464126		200	4
RBS432-40-24V AC	002464144		200	4
RBS432-31-230V AC	002464135		200	4
RBS432-31-24V AC	002464153		200	4
RBS432-22-230V AC	002464138		200	4
RBS432-22-24V AC	002464156		200	4
RBS432-2C-230V AC	002464141		200	4
RBS432-2C-24V AC	002464159		200	4

Sealing cover

Type	Code No.	Weight [g]	Packaging [pcs]
SC	002464160	3	2

*Size of one module - for covering 2-module sized RBS two pcs are needed, one for each side